



TITLE OF INVENTION

Adaptable Front End Bucket

CROSS REFERENCES TO RELATED APPLICATIONS

Not Applicable

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH

Not Applicable

REFERENCE TO APPENDIX

Not Applicable

BACKGROUND OF THE INVENTION

A. FIELD OF THE INVENTION

This is a way to improve a tractor blade by converting it into a bucket as well as a blade using this device.

B. PRIOR ART

Tractors are typically used to push debris and other items. They do not, however, serve as buckets to lift and eventually move material. The present device is an attachment to convert a tractor blade into a bucket temporarily.

The prior art in this area involves bucket attachments for tractor blades, which involve mechanical levers and other similar devices. The prior art generally describe devices, which are permanently attached to the tractor blade.

Representative examples of this prior art include Long, patent number 4,890,400, Funk, patent number 3,559,314, and Deyo patent number D425,527.

One of the disadvantages of the prior art is that the items

NO NEW MATTER IS BEING ADDED

1 must be permanently attached to the tractor blade. The current
2
3 device is lightweight and portable enough to be easily attached and
4
5 reattached at will. Additionally, no major alterations need to be
6
7 made to the tractor blade as this device is not meant to be a
8
9 permanent attachment.
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50

BRIEF SUMMARY OF THE INVENTION

1
2
3 This is a device, which has a flat base member, two side
4
5 panels and a means to secure the device to a tractor. Pieces of
6
7 angle rod are welded or attached to the side panels to provide
8
9 stability.

10
11 The base member is a flat, solid piece of metal. The base
12
13 member will be positioned generally perpendicular to the lower edge
14
15 of the blade of the tractor. When the device is installed, the
16
17 base member and the tractor blade form a scoop.

18
19 One end of a side panel is welded or connected to the base
20
21 member and the other end of the side panel is welded or connected
22
23 to a top servicing rod.

24
25 The side panels extend in a vertical direction from the base
26
27 member. The side panels are parallel to each other and extend the
28
29 height of the tractor blade. A top securing rod is inserted over
30
31 the top surface of the tractor blade and serves to secure its
32
33 position along the top edge of the tractor blade. Most tractor
34
35 blades are made such that the top edge forms a lip against which
36
37 the top securing rod would fit. If the top edge does not have a
38
39 lip one can be installed to accommodate the top securing rod of the
40
41 device.

42
43 On the bottom of the base member holes are placed at the
44
45 bottom of the side panels to accommodate a bottom securing rod,
46
47 which extends slightly more than the length of the tractor blade.
48
49 Cotter pins on both ends of the bottom securing rod would
50

1 secure the bottom securing rod in place.
2

3 In another embodiment the device is secured with pins, which
4
5 maintain the position of the device on the bottom.
6

7 Pieces of angle iron, which are on the inside surface of the
8
9 side panels keep the device in position while the device is in use
10
11 and prevent the device from tilting.
12

13 The device is designed to be portable and readily removed from
14
15 the tractor blade. It is contemplated that a variety of metals may
16
17 be used to construct the device. However, steel is probably
18
19 preferred for durability reasons.
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a perspective view of the device attached to the front of a tractor blade and the outline of a tractor.

Figure 2 is a front view of the device with the tractor not shown.

Figure 3 is a perspective view of the device with the tractor not shown.

Figure 4 is a cross section of the device as indicated by the 4-4 section on Figure 1.

Figure 5 is a perspective view of the device using pins to secure the device.

DETAILED DESCRIPTION OF THE EMBODIMENTS

According to Figure 3 this device consists of a base member 100, two end plates 200, a top securing rod 600 and a means to attach this particular device to a tractor blade 720 50. Figure 1, 2 The tractor itself and the tractor blade 720 50 are not claimed as part of this device. ~~Figure 4~~

Angle clips or brackets 300 are attached to the inside surface of the respective end plates 200 and lie flush with the edge of the respective end plate 200. The angle clips 300 allow this device to be secured in place and rest firmly against one side of the tractor blade 720 while the device is in use. The angle clips 300 are not attached to the tractor blade 720 when the device is installed but are merely used to maintain the position of the device relative to the tractor blade 720 to prevent titling or swaying of the device while in operation. Figure 1, 3

On the bottom of this device is a bottom removal securing rod 400, which is secured with a cotter pin 500 on both sides of the device. ~~(Figures 2, 4)~~ The bottom removal securing rod 400 is placed on the back surface 725 of ~~gives the device stability at the bottom surface of~~ the tractor blade 720 and secures the device in place. ~~Figure 4 rests against the bottom surface of the tractor blade.~~ The bottom securing rod 400 extends slightly ~~more than~~ beyond the length of the device and holes are positioned at the ends of the rod to install a cotter pin 500 at each end. Figure 1,

NO NEW MATTER IS BEING ADDED

1 A top bar 600 slips over the top of the tractor blade 720 and
2
3 hooks on the top edge or lip 705 of the tractor blade. Figure 4
4

5 The end plates 200, which are welded to the outside edges of
6
7 the base member 100, form the "bucket" or "scoop" of this
8
9 particular device when the device is installed. The end plates 200
10
11 extend vertically to slightly higher than the tractor blade 720.
12
13 When the device is installed, the length between the end plates 200
14
15 is slightly longer than the tractor blade 720 to complete the
16
17 "bucket".
18

19 A top rod 600 is used to connect the end plates 200 at the
20
21 top. The top rod 600 is inserted in the lip 705 of ~~over~~ the
22
23 tractor blade when the device is installed. Figure 4, 5 The
24
25 standard tractor blade 720 ~~500~~ is equipped with a lip 705, which
26
27 allows the top rod 600 to be held securely in place during normal
28
29 operation. The top rod 600 is welded to the interior surface of
30
31 the end plates 200. Figure 5
32

33 Figure 1 depicts how the device will be mounted on a tractor
34
35 blade 720 with a sketch of a tractor on this drawing.
36

37 Figure 2 depicts the various parts of the device as seen from the
38
39 front. According to Figure 2 the tractor blade 720 would occupy
40
41 the space between the top bar 600 and the bottom securing rod 400.
42

43 The outside edges of the tractor blade (not shown) would rest
44
45 against the angle clips 300 and be secured by the top rod 600 and
46
47 the removable securing rod 400 and cotter pins 500. Figure 2, 4
48
49 Two sets of angle clips are contemplated per end plate as shown in
50

1 Figures 2 and 3 to provide the required stability.

2
3 Because the device is meant to be portable and easily removed,
4
5 the device will be made of lightweight yet durable material.

6
7 It is contemplated that because of the environments, which
8
9 will be encountered, that the device will be constructed from
10
11 metals and preferably steel or aluminum.

12
13 **SECOND EMBODIMENT**

14
15 The device may also be secured at the bottom by pins 700
16
17 instead of a removable securing rod 400 and cotter pins 500.

18
19 Figure 5 Other means of attachment, which do not involve a
20
21 bottom securing rod could also include nuts and bolts.

22
23 In this embodiment the top lip 705 of the tractor blade 720 is
24
25 placed over the bar 600 of the device. The bottom surface 100 and
26
27 edges 200 are identical in this embodiment. Pins 700 are inserted
28
29 through holes 712, which have been provided so that the pin 700
30
31 will be positioned on the back surface 725 of the tractor blade
32
33 720. Figure 5 In the second embodiment the pins 700 take
34
35 the place of the removable securing rod 400 in the prior
36
37 embodiment.

38
39 In the second embodiment the device operates in the same
40
41 manner but the means to secure the device at the bottom edge is
42
43 different.